

## Description:

Fuel-efficient, fuel-saving motor oil SAE 0W20 developed using the latest technologies, based on specially selected synthetic base oils and a well-balanced set of advanced additives to provide the following properties:

- high fuel economy
- high and stable viscosity index
- good shear stability
- very fast cold start, even at extremely low temperatures
- reliable lubricating film at very high temperatures
- excellent detergency and dispersancy
- effective protection against wear, corrosion, and foaming

## Application:

Fuel-efficient, fuel-saving motor oil specially designed for gasoline and diesel engines of Volvo vehicles where the manufacturer requires a product meeting the VCC RBS0-2AE specification with a viscosity of SAE 0W20.

## Approvals and Specifications:

ACEA: C5

API: SP

FIAT: 9.55535-DSX

VOLVO: VCC RBS0-2AE



## Characteristics:

Density at 15°C, kg/l	0,843
Viscosity at -35°C, mPa·s	5750
Viscosity at 40°C, mm <sup>2</sup> /s	45.90
Viscosity at 100°C, mm <sup>2</sup> /s	8.70
Viscosity index	173
Cleveland flash point, °C,	220
Pour point, °C	-45
Total base number, mg KOH/g	7.7
Sulfated ash, %	0.80

The listed typical physicochemical characteristics are for reference only, meet approval standards, and are not mandatory technical conditions for production and sale. Due to ongoing product research and development, the information contained herein may be changed without notice