AREOL ECO ENERGY DX1 5W-30

AREOL
PREMIUM QUALITY
IN EVERY DROP

Description:

An advanced resource conserving motor oil based on specially selected synthetic base oils with a high viscosity index and a balanced additive package. The composition of the product provides high oxidation resistance, excellent resistance to high temperatures and is distinguished by strong cleaning performance. An innovative additive technology prevents Low Speed Pre-Ignition (LSPI), prolonging engine life.

Application:

It is recommended for use in petrol engines in passenger cars, where the manufacturer requires an oil that meets the GM dexos1™ Gen 3 standard. Suitable for hybrid vehicles, provided OEM specifications are met.

Approvals and Specifications:

API SQ RESOURCE CONSERVING
API SP RESOURCE CONSERVING
ILSAC GF-7A
ILSAC GF-6A
GM DEXOS 1 GEN 3
CHRYSLER MS6395
FORD WSS-M2C946-A
FORD WSS-M2C946-B1
FORD WSS-M2C961-A1

Specifications:

Density at 15 °C, Kg/L	0.847
Viscosity at 40 °C, mm2/s	60.3
Viscosity at 100 °C, mm2/s	10.7
Viscosity index	168
Cleveland flash point, °C	221
TBN, mgKOH/g	8.5
Sulfated ash, %	0.78
Pour point, °C	-36

The specified typical physical and chemical characteristics are for reference only, fall within standard tolerance ranges, and do not constitute mandatory technical specifications for production or sale. Due to ongoing product research and development, the information contained herein is subject to change without notice.